



# DRIED SAND

Washed and dried sand meeting AS3700 (requirement for bricklaying sand)  
Covers approx 3.5m<sup>2</sup> per 20kg bag (3mm gap, brick shaped pavers)  
Less clay and deleterious substances

**CEMENT AUSTRALIA**<sup>®</sup>



# DRIED SAND

- ✓ Washed and dried sand meeting AS3700 (required for bricklaying sand)
- ✓ Covers approx 3.5m<sup>2</sup> per 20kg bag (3mm gap, brick shaped pavers)
- ✓ Less clay and deleterious substances
- ✓ Multipurpose use

Build with Confidence

[cementaustralia.com.au](http://cementaustralia.com.au) or call 1300 CEMENT (1300 236 368)

**MADE**  
Right Here

**CEMENT AUSTRALIA**<sup>®</sup>



Dried Sand is a quality factory dried sand designed for use on a range of home, garden and building applications including:

- ✓ Agricultural uses
- ✓ Artificial lawns and landscaping projects
- ✓ Animal litter
- ✓ Backfill and trenchfill
- ✓ Bird aviaries and barns stalls
- ✓ Brick, slab and block paving
- ✓ Concrete and grout mixes
- ✓ Grease traps and BBQ trays
- ✓ Hobby modelling
- ✓ Mortar mixes
- ✓ Paver infill
- ✓ Potting mix blends
- ✓ Render

## SUGGESTED MIX RATIOS

APPLICATION	CEMENT	SAND	AGGREGATE	20kg BAGS PER M <sup>3</sup>
Concrete – Improved Water Tightness – High Strength	1	1.5	3	17
Concrete – Paths and Driveways	1	2	3	16
Concrete – Foundations, Footings	1	3	3	13
Mortar (General Purpose)	1	4	-	15
Mortar (Enhanced Workability)	1	6	-	8
		+1 Hydrated Lime		
Render	1	3	-	20

*Please note: Colour results may vary - the colour of the finished product may vary due to natural differences in raw materials.*

## STORAGE, HANDLING and SAFETY

- Care should be taken when lifting bagged products as personal injury may occur. It is suggested that when lifting bagged materials, the load is shared with another person.
- Dried Sand should be stored in a dry place, off the ground and protected from the ingress of moisture.

## HINTS and TIPS

- One 20kg bag of Dried Sand covers approximately 3.5m<sup>2</sup> at a 3mm gap (brick shaped pavers)
- One 20kg bag of Dried Sand covers approximately 12m<sup>2</sup> at a 3mm gap (400mm square pavers)

Item Code 17734  
Cement Australia  
Dried Sand 20kg



### PRODUCT DISCLAIMER

Recommendations regarding the use of this product are to be taken as a guide only. If in doubt contact Cement Australia Pty Limited ("Cement Australia") or seek professional advice. To the extent permitted by law, Cement Australia excludes all implied warranties, conditions and guarantees imposed by legislation. Cement Australia excludes all liability for loss, damage or injury arising from use of the product (i) otherwise than in accordance with the recommendations or (ii) for purposes other than those for which it is ordinarily acquired. For all other loss, damage or injury arising from the use of this product, to the extent permitted by law Cement Australia's liability is limited, at its discretion, to refunding the cost of the product or resupplying the product or equivalent product.

